

KERN ORL 94LM



Digital refractometer with pre-installed scales for refractive index measurements and the food application area



Category

Brand	Optics
Product category	Refractometer
Product group	Digital refractometer
Product family	ORL-B

Measuring System

Measurement temperature [Min] (°C)	0 °C
Measurement temperature [Max] (°C)	40 °C

Precision	0,0002 nD
	0,1 %
	0,2 %
	0,2 %
	0,2 %
	0,2 %
	0,2 %
	0,2 %
	2 ‰
	0,002 sg

Measuring method	Total reflection
------------------	------------------

Measuring range Brix [Min]	0 %
----------------------------	-----

Scales	Refractive index
	Brix
	Fructose (Fruchtzucker)
	Glucose (Traubenzucker)
	Laktose (Milchzucker)
	Maltose (Malzzucker)
	Dextran
	Salt (NaCl)
	Salz (NaCl) ‰
	spec. gravity

Measuring ranges	1,3330 nD - 1,5290 nD
	0 % - 94 %

	0,0 % - 68,9 %
	0,0 % - 59,9 %
	0,0 % - 16,5 %
	0,0 % - 15,6 %
	0,0 % - 10,6 %
	0,0 % - 28,0 %
	0 ‰ - 280 ‰
	1,000 sg - 1,220 sg

	0,0001 nD
	0,1 %
	0,1 %
	0,1 %
	0,1 %
	0,1 %
	0,1 %
	0,1 %
	1 ‰
	0,001 sg

Readout Brix	0,1 %
--------------	-------

Automatic temperature compensation (ATC)	✓
--	---

Accuracy Brix	±0,1 %
---------------	--------

Measuring range refractive index [Min]	1,3330 nD
--	-----------

Measuring range refractive index [Max]	1,5290 nD
--	-----------

Readout refractive index	0,0001 nD
--------------------------	-----------

Accuracy refractive index	±0,0002 nD
---------------------------	------------

Measuring range dextran [Min]	0 %
-------------------------------	-----

Scale for Refractive index	✓
----------------------------	---

Measuring range dextran [Max]	11 %
-------------------------------	------

Readout dextran	0,1 %
-----------------	-------

Accuracy dextran	±0,2 %
------------------	--------

Scale for dextran	✓
-------------------	---

Measuring range fructose (fruit sugar) [Min]	0 %
--	-----

Measuring range fructose (fruit sugar) [Max]	69 %
--	------

Readout fructose (fruit sugar)	0,1 %
--------------------------------	-------

Accuracy fructose (fruit sugar)	±0,2 %
---------------------------------	--------

Measuring range glucose (fruit sugar) [Min]	0 %
---	-----

Measuring range glucose (fruit sugar) [Max]	60 %
---	------

Readout glucose (fruit sugar)	0,1 %
-------------------------------	-------

Accuracy glucose (fruit sugar)	±0,2 %
--------------------------------	--------

Scale for fructose (fruit sugar)	✓
----------------------------------	---

Scale for glucose (fruit sugar)	✓
---------------------------------	---

Measuring range lactose (milk sugar) [Min]	0 %
--	-----

KERN ORL 94LM



Digital refractometer with pre-installed scales for refractive index measurements and the food application area

Measuring range lactose (milk sugar) [Max]	17 %
Readout lactose (milk sugar)	0,1 %
Accuracy lactose (milk sugar)	±0,2 %
Measuring range maltose (malt sugar) [Min]	0 %
Measuring range maltose (malt sugar) [Max]	16 %
Readout maltose (malt sugar)	0,1 %
Accuracy maltose (malt sugar)	±0,2 %
Scale lactose (milk sugar)	✓
Scale maltose (malt sugar)	✓
Measuring range salinity (NaCl) % [Min]	0 %
Measuring range salinity (NaCl) % [Max]	28 %
Readout salinity (NaCl) %	0,1 %
Accuracy salinity (NaCl) %	±0,2 %
Measuring range salinity (NaCl) ‰ [Min]	0 ‰
Measuring range salinity (NaCl) ‰ [Max]	280 ‰
Readout salinity (NaCl) ‰	1 ‰
Accuracy salinity (NaCl) ‰	±2 ‰
Scale salinity (NaCl) %	✓
Scale salinity (NaCl) ‰	✓
Measuring range salinity (spec. weight) [Min]	1,000
Measuring range salinity (spec. weight) [Max]	1,220
Readout salinity (spec. weight)	0,001
Accuracy salinity (spec. weight)	±0,002
Scale salinity (spec. weight)	✓
Appropriate calibration liquid	0 % (distilled water)
Measuring range Brix [Max]	94 %
Brix scale	✓
Area of application	Food

Construction

Dimension (W×D×H)	180×100×55 mm
Refractometer type	Desktop refractometer
Scale - Display type	Digital
Prism lid	✓
Material prism	Sapphire

Functions

Color display	✓
Averaging measurement	✓
Averaging measurement amount	15

Automatic temperature compensation	✓
IP protection - complete device	IP43
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min

Interface

Interfaces	USB 2.0
------------	---------

Power Supply

Supplied power supply	Power supply unit
Plug-in power supply type	USB including power supply
Plug-in power supply / adapter for countries - included with the delivery	EURO
Plug-in power supply / adapter for countries - optional	EURO UK
Input voltage power supply / power [Max]	100 - 240 V AC 50/60 Hz 0,35 A
Input voltage device / power [Max]	5 V DC 2,0 A
Power socket for mains adapter	USB B
Battery connection	Pad + Spring

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓
---------	---

Services (optional)

Article number for factory calibration	961-290
--	---------

Packing & Shipping

Dimensions transport container (W×D×H)	300×150×100 mm
Delivery time	1 d
Dimensions packaging (W×D×H)	300×150×100 mm
Shipping method	Parcel service
Net weight approx.	0,40 kg
Gross weight approx.	1,00 kg
Shipping weight	1 kg

Product information

GTIN/EAN number	4045761489455
REACH classification	no prohibited substances

KERN ORL 94LM



Digital refractometer with pre-installed scales for refractive index measurements and the food application area

Pictograms

STANDARD



OPTION

